IN THE CLAIMS:

<u>Please add the following newly-drafted Claims 25 through 27::</u>

1   25.   A data conversion system for integrating Hyper Text Markup Language (HTML)

2 documents from a source on the Internet into a format suitable for enabling a user interaction

3 with a video broadcast receiver comprising:

4   a remote controller that enables a user to interact with a video display unit; and

5   a data conversion apparatus for converting the HTML documents including,

6   document storing means for storing a plurality of HTML documents from

7 a source on the Internet, each of the HTML documents include at least a character

8 string and at least a piece of image information, wherein at least one of the

9 character string and the piece of image information includes a piece of link

10 destination information which specifies another HTML document as a link

11 destination;

12   supplementary design storing means for storing a list of supplementary

13 designs with serial numbers respectively related to the supplementary designs;

14   display image element generating means for reading the character string

15 and the piece of image information from the document storing means and

16 converting the character string and the piece of image information into respective

17 display image elements, wherein the display image elements are bit-mapped

18 graphics;

19   supplementary design adding means for reading a supplementary design

20 corresponding to the piece of link destination information specifying the other

21   document as the link destination from the supplementary design storing means

22   and adding the supplementary design to a corresponding display image element in

23   the bit-mapped graphics;

24   display link destination information converting means for converting the

25   piece of link destination information specifying the other document as the link

26   destination into a piece of display link destination information, the piece of

27   display link destination information being related to a serial number

28   corresponding to the supplementary design added by the supplementary design

29   adding means, wherein the piece of display link destination information specifies,

30   as a link destination, another display image; and

31   display image generating means for generating a video display image for

32   the video display unit which is composed of the display image elements wherein

33   the user can activate the remote controller to indicate selection of a specific

34   supplementary design in the displayed video image to link to another display

35   image that will be generated.

1   26.   The data conversion system of Claim 25, wherein the supplementary design

2 storing means includes:

3   a maximum number storing unit for storing a maximum number of the

4 supplementary designs in the display image, wherein the display image generating means

5 further includes:

6   a display image generating unit for generating the display image by

7 arranging the display image elements in the display image according to the

8 display positions;

9   a maximum number judging unit for judging whether the number of the

10   supplementary designs to be arranged in the display image exceeds a maximum

11   number; and

12   a display image dividing unit for, when the maximum number judging unit

13   judges that the number of the supplementary designs exceeds the maximum

14   number, sending an instruction to the display image generating unit to divide the

15   display image into a plurality of display sub-images so that supplementary

16   designs less than the maximum number are added to each of the plurality of

17   display sub-images divided from the display image, wherein the display image

18   generating unit generates the plurality of display sub-images according to the

19   instruction.

1   27.   The data conversion system of Claim 26, wherein:

2   the display link destination converting means further includes:

3   a display link destination sub-information generating unit for generating a

4   plurality sets of pieces of display link destination sub-information which

5   respectively correspond to the plurality of display sub-images generated by the

6   display image generating unit.

127